


**TOP VIEW**




**SECTION B-B**
**END VIEW**






**SECTION A-A**
**SIDE VIEW**







**INSIDE BOX**




**INSIDE LID**

POLYCARBONATE
VERSION ONLY
c UL US LISTED
FILE #E65324
TYPE 4,4X,6,6P

Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory (modshop@hammfg.com) for quotes
Solid models of this enclosure available in .stp or .x_t
(Part number and text placement/orientation on our products are subject to change, we do not recommend using them as a locating reference for modification purposes)

| NOTE |
|---|
| 6 cover screws, and<br>preformed silicone gasket.<br>General Purpose ABS version is not UL approved. (Matl UL94 - HB)<br>Polycarbonate version is UL 508A approved. (Matl UL94 - 5VA @ 3mm) |
| **Recommended Cover screw torque -- 43-57 ozf-in (30-40 cN-m)** |

| 1555VA | |
|---|---|
| **1555VA Regular Enclosure** | |
| General Purpose ABS RAL-7035 | 1555VAGY |
| Polycarbonate RAL-7035 | 1555VA2GY |
| **ACCESSORIES** | |
| Steel Inner Panels | 1554VAPL |
| Steel Panel / P.C. Board Screw [M3-0.5 x 8mm Plated] (Pkg 100) | 1591MM100 |
| Steel Panel / P.C. Board Self Tapping Screw [#6 X 1/4" (6.4mm) Plated] (Pkg 100) | 1598ATS100 |
| Stainless Steel Cover Screws [M4-0.7 X 25mm] (Pkg 50) | SC583-50 |
| Silicone Pre-formed Gasket Black (Pkg 2) | 1554VAGASKET |

**Dimensions:**
mm
[inches]

1555VA
www.hammondmfg.com

28.02.2020