


2. ELECTRICAL SCHEMATIC:



L: 1.7mH
Cx1: 1.0uF
Cx2: 0.68uF
Cy1: 10000pF
Cy2: 0.047uF
R: 330KΩ

20DRT1W3S

Units: mm
Full Scale

3. ELECTRICAL CHARACTERISTICS:

- 3-1. VOLTAGE RATING 250VAC
- 3-2. CURRENT RATING
A. AT 250VAC 20 A RMS Max.
- 3-3. OPERATING FREQUENCY..... 50/60 Hz
- 3-4. LEAKAGE CURRENT: EACH LINE TO GROUND
A. @250VAC 60Hz 10.0 mA Max.
- 3-5. HIPOT RATING (FOR ONE MINUTE)
A. LINE TO GROUND 2250VDC
B. LINE TO LINE 1450VDC

3-6. MINIMUM INSERTION LOSS IN dB: (AT 50 OHM SYSTEM)

FREQ. MHz	.01	.05	.10	.15	.50	1.0	5.0	10	30
COM. MODE dB	5	10	40	50	75	75	70	70	45
DIF. MODE dB	2	5	20	35	60	60	55	55	55

- 3-7. AMBIENT TEMPERATURE 40°C
- 3-8. OPERATING TEMPERATURE -25°C TO +85°C