



ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHING 0.004 GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN, THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR.



FACE RUNOUT (WITH INDICATOR MOUNTED STATIONARY RELATIVE TO SHAFT) MUST NOT EXCEED 0.004 T.I.R.  
 ECCENTRICITY OF THIS SURFACE (WITH INDICATOR MOUNTED STATIONARY RELATIVE TO SHAFT) MUST NOT EXCEED 0.004 T.I.R.

- NOTES:
1. DIMENSIONS CAN BE CHANGED BY MANUFACTURER WITHOUT NOTICE.
  2. DIMENSIONS DO NOT IMPLY TOLERANCE.

J047
Units: inches [mm]
Scale: Full
<b>MARATHON AC INDUCTION MOTOR, GENERAL PURPOSE PUMP, 1/3 HP, 3-PH, 208-230/460 VAC, 3450 RPM, DP, 56J FRAME, ROLLED STEEL, RIGID BASE/C-FACE MOUNT</b>
<b>AUTOMATIONDIRECT</b> .com