


PART NUMBER	L	DATUM TO CENTER OF MASS DISTANCE		
		A	B	C
LAHP-33TM210SF	300.0 [11.81]	150.0 [5.91]	12.7 [0.5]	30.0 [1.18]
LAHP-33TM310SF	400.0 [15.75]	200.0 [7.87]	12.7 [0.5]	30.0 [1.18]
LAHP-33TM410SF	500.0 [19.69]	250.0 [9.84]	12.7 [0.5]	30.0 [1.18]
LAHP-33TM510SF	600.0 [23.62]	300.0 [11.81]	12.7 [0.5]	30.0 [1.18]
LAHP-33TM610SF	700.0 [27.56]	350.0 [13.78]	12.7 [0.5]	30.0 [1.18]
LAHP-33TM810SF	900.0 [35.43]	450.0 [17.72]	12.7 [0.5]	30.0 [1.18]
LAHP-33TM910SF	1,000.0 [39.37]	500.0 [19.69]	12.7 [0.5]	30.0 [1.18]

= CENTER OF MASS - CALCULATED WITH CARRIAGE IN THE CENTER OF TRAVEL (SYMBOL POSITION ON DRAWING IS REPRESENTATIVE AND NOT EXACT)



NOTES:

1. DIMENSIONS CAN BE CHANGED BY MANUFACTURER WITHOUT NOTICE.
2. DIMENSIONS DO NOT IMPLY TOLERANCE.

LAHP-33TMXXXXSF
Units: mm [inches] Scale: Full
SUREMOTION LINEAR SLIDE
AUTOMATIONDIRECT .com