

SECTION A-A









SECTION B-B







THIS DRAWING IS THE SOLE AND EXCLUSIVE PROPERTY OF ROBROY ENCLOSURES. NO PART OF THIS DRAWING MAY BE REPRODUCED, DISTRIBUTED, OR PUBLICALLY DISPLAYED IN ANY FORM OR BY ANY MEANS WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROBROY ENCLOSURES. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS. COPYRIGHT © 2020 ROBROY ENCLOSURES

SPECIAL REQUIREMENTS

CNC:
1. CONTACT ENGINEERING FOR FIRST RUN INSPECTION

ASSEMBLY:
1. INSTALL (1) QT-LATCH (RMEMKSE) AS SHOWN PER STANDARD PROCESS
2. INSTALL (2) (RMLATNLL150) & (2) (RMLATNLL150WT) LATCHES ON BOX & (4) KEEPERS (RMKEEPLL150WT) ON COVER USING (16) RIVET (RMRIV48) PER STANDARD PROCESS

NEMA 250: TYPE 1, 3, 3R, 4X, 12 IEC 60529: IP66	STANDARD P/N: T242410HWTSL	ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED	TOLERANCES UNLESS SPECIFIED .XX ± 0.03 .XXX ± 0.010
COLOR: GLACIER GRAY (WPR3X13) COLOR STANDARD: PANTONE 428 C	CUSTOMER DWG:		

MATERIAL: FIBERGLASS REINFORCED POLYESTER (FRP)

REVISION HISTORY

REV	DESCRIPTION	DATE	ENG
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

AttaBox — A ROBROY ENCLOSURES™ BRAND

Robroy Enclosures
500 Maple Street
Belding, Michigan 48809
Phone: 616-794-0700
Fax: 616-749-3378

DRAWN BY	DATE	CUSTOMER	DWG
AA	8/17/20		T242410HWTSL
SCALE		DESCRIPTION	PART NUMBER
DO NOT SCALE		STANDARD ENCLOSURE	ATT242410HWTSL