





#### NOTES:

1. ALL DIMENSIONS ARE FROM OUTSIDE UNLESS OTHERWISE NOTED (1/5).
2. ENCLOSURE IS FABRICATED FROM 12 GA. 304 STAINLESS STEEL.
3. ALL SEAMS ARE CONTINUOUSLY WELDED & GROUND SMOOTH.
4. DOOR IS SEALED WITH FOAM-IN-PLACE GASKET.
5. DOOR IS SECURED SHUT WITH A 3-POINT 316 S.S. PADLOCKABLE HANDLE WITH BUILT IN DEFEATER.
6. A 10 GA. CARBON STEEL BACK PANEL IS INSTALLED PER DRAWING.
7. FINISH: EXTERIOR - STANDARD GRAINED FINISH.  
INTERIOR - STANDARD COMMERCIAL FINISH.  
PANEL - WHITE POLYESTER POWDER (SMOOTH).
8. ENCLOSURE IS RATED UL TYPE 4X.



REVISION HISTORY			
REV	DESCRIPTION	BY	DATE
A	ECO# 20160606-1L	WF	05/09/2017



PART#: WA84XM3924SSN4  
(DATA SUBJECT TO CHANGE WITHOUT NOTICE)

THIS DRAWING IS PROPERTY OF HUBBELL INC. WIEGMANN  
ALL INFORMATION IS PROPRIETARY AND NOT TO BE DUPLICATED