


TABLE A

PART NO.	LENGTH
ZL-BX-CBL15-1P	1.0m (3.3ft)
ZL-BX-CBL15-2P	2.0m (6.6ft)



PIN-OUT DIAGRAM

P1	P2
15	BLUE
14	PINK
13	LIGHT BLUE
12	LIGHT GREEN
11	GRAY
10	YELLOW
9	PURPLE
8	GREEN
7	ORANGE
6	RED
5	BROWN
4	BLACK
3	ORANGE/BLACK
2	RED/BLACK
1	WHITE
NC	GREEN/BLACK
NC	GRAY/BLACK
NC	YELLOW/BLACK
NC	PURPLE/WHITE
NC	GREEN/WHITE
NC	ORANGE/WHITE
NC	RED/WHITE
NC	BROWN/WHITE
NC	BLACK/WHITE

NOTES:

1. CABLE: 24 CONDUCTOR, 24 AWG, PVC JACKET INSULATION RATING 80°C (176°F), 300V
2. CURRENT: 2A PER CONDUCTOR, 36A MAXIMUM CABLE CURRENT
3. VOLTAGE
 - * 240V AC/DC RATED OPERATING VOLTAGE
 - * 265V AC/DC MAXIMUM VOLTAGE
4. OPERATING TEMPERATURE: 0-60°C (32-140°F)
5. P1 CONNECTOR: 15 POSITION OVERMOLDED TERMINAL BLOCK FOR BRX PLC
6. P2 CONNECTOR: 24 TINNED PIG-TAIL LEADS
7. MINIMUM BEND RADIUS: 65.6MM [2.58IN]

NC WIRES MUST BE CUT BACK AND HEAT SHRINKED

ZL-BX-CBL15-nP	
Rev: C	Date: 4/12/2017
Units: mm [inches]	
Scale: 1:1	
ZIPLink Connector Module Cable	
Automation	Direct