


TABLE A

PART NO.	LENGTH
ZL-BXEM-CBL20-1P	1.0m (3.3ft)
ZL-BXEM-CBL20-2P	2.0m (6.6ft)

P1  
PLC CONNECTION



PIN-OUT DIAGRAM

P1	P2
1	BLUE
2	PINK
3	LIGHT BLUE
4	LIGHT GREEN
5	GRAY
6	YELLOW
7	PURPLE
8	GREEN
9	ORANGE
10	RED
11	BROWN
12	BLACK
13	ORANGE/BLACK
14	RED/BLACK
15	WHITE
16	GREEN/BLACK
17	GRAY/BLACK
18	YELLOW/BLACK
19	PURPLE/WHITE
20	GREEN/WHITE
	ORANGE/WHITE
	RED/WHITE
	BROWN/WHITE
	BLACK/WHITE

## NOTES:

1. CABLE: 24 CONDUCTOR, 24 AWG, PVC JACKET INSULATION RATING 80°C (176°F), 300V
2. CURRENT: 2A PER CONDUCTOR, 40A MAXIMUM CABLE CURRENT
3. VOLTAGE
  - 240V AC/DC RATED OPERATING VOLTAGE
  - 265V AC/DC MAXIMUM VOLTAGE
4. OPERATING TEMPERATURE: 0-60°C (32-140°F)
5. P1 CONNECTOR: 20 POSITION OVERMOLDED TERMINAL BLOCK FOR BRX PLC
6. P2 CONNECTOR: 24 TINNED PIG-TAIL LEADS
7. MINIMUM BEND RADIUS: 65.6MM [2.58IN]

ZL-BXEM-CBL20-nP	
Rev: B	Date: 4/12/2017
Units: mm [inches]	
Scale: 1:1	
ZIPLink Connector Module Cable	
	Automation Direct