


TABLE A

PART NO	LENGTH
ZL-D0-CBL24	0.5m [1.6 ft]
ZL-D0-CBL24-1	1.0m [3.3 ft]
ZL-D0-CBL24-2	2.0m [6.6 ft]



PIN-OUT DIAGRAM

P1	P2	P1	P2
12 BLUE	2	24 ORANGE/BLACK	14
11 PINK	3	23 RED/BLACK	15
10 LIGHT BLUE	4	22 WHITE	16
9 LIGHT GREEN	5	21 GREEN/BLACK	17
8 GRAY	6	20 GRAY/BLACK	18
7 YELLOW	7	19 YELLOW/BLACK	19
6 PURPLE	8	18 PURPLE/WHITE	20
5 GREEN	9	17 GREEN/WHITE	21
4 ORANGE	10	16 ORANGE/WHITE	22
3 RED	11	15 RED/WHITE	23
2 BROWN	12	14 BROWN/WHITE	24
1 BLACK	1	13 BLACK/WHITE	13

## NOTES:

1. CABLE – 24 conductor, 24 AWG, PVC jacket insulation rating 80°C (176°F), 300V
2. CURRENT – 0.5A per conductor, 32A maximum cable current
3. VOLTAGE – 240V AC/DC rated operating voltage 265V AC/DC maximum voltage
4. OPERATING TEMPERATURE – 0–60°C (32–140°F)
5. P1 and P2 CONNECTOR – 24-pin receptacle equivalent to Molex Micro-Fit3.0 part # 43025–2400
6. MINIMUM BEND RADIUS – 80 mm [3.15 in]

ZL-D0-CBL24-n	
Rev: original	Date: 07/2009
Units: mm [inches]	
Scale: .03940	
ZIPLINK DL05/DL06 Cable	
AUTOMATIONDIRECT.com	