


TABLE A

PART NO	LENGTH
ZL-D0-CBL24-L	0.5m [1.6 ft]
ZL-D0-CBL24-1L	1.0m [3.3 ft]
ZL-D0-CBL24-2L	2.0m [6.6 ft]



PIN-OUT DIAGRAM

P1		P2		P1		P2	
12	BLUE	1		24	ORANGE/BLACK	13	
11	PINK	3		23	RED/BLACK	5	
10	LIGHT BLUE	4			WHITE		
9	LIGHT GREEN	2		22	GREEN/BLACK	6	
8	GRAY	15		21	GRAY/BLACK	14	
7	YELLOW	16		20	YELLOW/BLACK	17	
6	PURPLE	7		19	PURPLE/WHITE	18	
5	GREEN	9		18	PURPLE/WHITE	19	
4	ORANGE	10		17	GREEN/WHITE	11	
3	RED	8		16	ORANGE/WHITE	12	
2	BROWN	21		15	RED/WHITE	20	
1	BLACK	22		14	BROWN/WHITE	23	
				13	BLACK/WHITE	24	

NOTES:

1. CABLE – 24 conductor, 24 AWG, PVC jacket insulation rating 80°C (176°F), 300V
2. CURRENT – 0.5A per conductor, 32A maximum cable current
3. VOLTAGE – 240V AC/DC rated operating voltage 265V AC/DC maximum voltage
4. OPERATING TEMPERATURE – 0–60°C (32–140°F)
5. P1 and P2 CONNECTOR – 24-pin receptacle equivalent to Molex Micro-Fit3.0 part # 43025–2400
7. MINIMUM BEND RADIUS – 80 mm [3.15 in]

ZL-D0-CBL24-nL	
Rev: original	Date: 07/2009
Units: mm [inches]	
Scale: .03940	
ZIPLINK DL05/DL06 Cable	
AUTOMATIONDIRECT.com	