


4 MOUNTING FEET REQ'D. PER KIT



4 MOUNTING SCREWS REQ'D. PER KIT
RMSC10-32x7/16FHPH SCREW 18-8 STAINLESS STEEL

NOTES

DIMENSIONS ARE SHOWN AS MOLDED.

DRAFT IS 1.5 DEGREES UNLESS SPECIFIED OTHERWISE.

ALL EDGES SHALL BE FILLETED EXCEPT BACK EDGE.

HOLE FILLET RADIUS IS 0.010"; OTHER EDGE FILLET RADIUS IS 0.030".

CRITICAL INSPECTION DIMENSIONS ARE WITHIN A BOX.

EJECTOR PINS TO BE FLUSH TO .010 BELOW SURFACE

VOLUME = 0.478 CU. IN.

NOTES:

NOTES:					COLOR : GLACIER GRAY RR3013			TOLERANCES TWO PLACE THREE PLACE							
KIT INCLUDES INST. SHEET, SCREWS, MTG FT, SUITABLE PLASTIC BAG								UNLESS SPECIFIED $\pm .020$ $\pm .005$							
MATERIAL: ISO POLYESTER SMC OR EQUIV RR3xxxx OR EQUIV UL746 APPROVED MATERIAL					DR. BY ZJB		DATE 11/26/02		HUBBELL WIEGMANN						
LET.		REVISION RECORD		DATE		BY		CHD.			CHK. BY		DATE		
A		UPDATED MATL. INFO. DIA WAS .22 ,WAS9/16		5/7/04 8/18/04		MJ MJ					APD. BY		DATE		
B		SCREW DIA. WAS .48		8/18/04		MJ									
C		TOLERANCE ADDED TO Ø0.210		2/23/05		GF				SCALE D. N. S.		PART NAME ENCLOSURE MOUNTING FOOT KIT		PART NO. HW-MGFTKIT	